



<https://forklift-manuals.jimdo.com>

NORTH AMERICA | CONSTRUCTION RANGE



Introducing the world's best construction equipment

From the time that Joseph Cyril Bamford founded JCB in a small garage in 1945, we've worked hard to earn a reputation for quality and innovation. While the company has grown to more than 10,000 people and 22 manufacturing facilities on four continents, those two key characteristics remain at the core of everything we do.

That spirit has driven JCB to many notable accomplishments over the years. It led the company to pioneer the backhoe loader in 1953, introduce the world's first telehandler in 1977 and launch the world's fastest production tractor in 1991. It also fueled JCB's moves to revolutionize the skid steer market, first in 1993 with the single-arm Powerboom™ and side-door entry to create the world's safest skid steers and compact track loaders, and then in 2017 with the Teleskid, the world's only skid steer and compact track loader with a telescopic boom.

Today, JCB machines are enabling greater productivity in every industry—from construction to agriculture, road building, defense, logistics and waste management—which is why JCB is the global leader in numerous equipment categories, including telescopic handlers and backhoe loaders.

JCB products are sold and supported by a network of 2,000 dealer locations in more than 150 countries and a state-of-the-art global distribution system that dispatches more than one million genuine parts and attachments every week.

JCB North America is headquartered near Savannah, Georgia, where the company manufactures compact track loaders, skid steer loaders and telescopic handlers for construction and agricultural applications. Additionally, JCB North America is the global headquarters for JCB Government & Defense, which manufactures bespoke military and commercial-off-the-shelf solutions for the U.S. military and allies around the world.

For all of the accomplishments, however, and all that the company aims to achieve in the future, it is JCB's world-renowned customer service that is most important. You can trust JCB to be there for you, wherever you are in North America and the world.

HYDRADIG

THE JCB HYDRADIG WHEELED EXCAVATOR AND TOOL CARRIER IS DESIGNED WITHOUT COMPROMISE AND BUILT FOR PURPOSE. WITH THE ENGINE, TANKS AND ANCILLARIES POSITIONED WITHIN THE CHASSIS, JCB HYDRADIG IS FIRST FOR VISIBILITY, STABILITY, MANEUVERABILITY, MOBILITY AND SERVICEABILITY.



		110W
Operating weight	lb (kg)	25,007 (11,343)
Gross engine power	hp (kW)	109 (81)
Dig depth	ft-in (mm)	14-6 (4,410)
Dig reach	ft-in (mm)	26-4 (8,020)
Machine variants		TAB
Travel speed	mph (km/h)	25 (40)

COMPACT EXCAVATORS

JCB COMPACT EXCAVATORS OFFER UNMATCHED PERFORMANCE AND RELIABILITY, AND INNOVATIVE FEATURES FOR GREATER COMFORT AND EASIER SERVICING. IN ADDITION, JCB COMPACT EXCAVATORS ARE EASY TO TRANSPORT AND HIGHLY MANEUVERABLE WITHIN CONFINED JOB SITES.



<https://forklift-manuals.jimdofree.com>

		18Z-I	19C-I	8,029 CTS	45Z-I	48Z-I	55Z-I
Transport weight	lb (kg)	3,690 (1,674)	4,134 (1,875)	6,156 (2,792)	9,700 (4,400)	10,277 (4,662)	11,543 (5,236)
Operating weight standard arm	lb (kg)	3,856 (1,749)	4,211 (1,910)	6,321 (2,867)	9,866 (4,475)	10,564 (4,792)	11,830 (5,366)
Gross engine power	hp (kW)	23.1 (17.2)	23.1 (17.2)	32.7 (24.4)	48.3 (36)	48.3 (36)	48.3 (36)
Dig depth (dozer down)	ft-in (mm)	7-11 (2,167)	7-11 (2,167)	10-0 (3,048)	11-11 (3,386)	11-11 (3,386)	12-7 (3,871)
Ground-level reach	ft-in (mm)	12-7 (3,871)	12-7 (3,871)	15-3 (4,663)	18-8 (5,730)	18-8 (5,730)	19-8 (6,035)
Dump height	ft-in (mm)	8-6 (2,621)	8-6 (2,621)	10-7 (3,261)	13-1 (3,993)	13-1 (3,993)	14-0 (4,267)
Bucket breakout force	lbf (kN)	4,046 (18)	4,046 (18)	5,170 (23)	8,542 (38)	8,542 (38)	9,442 (42)

		57C-I	67C-I	85Z-I	86C-I	90Z-I	100C-I
Transport weight	lb (kg)	11,801 (5,353)	14,738 (6,685)	18,133 (8,225)	18,795 (8,525)	18,605 (8,439)	21,087 (9,565)
Operating weight standard arm	lb (kg)	12,087 (5,483)	14,903 (6,760)	18,298 (8,300)	18,960 (8,600)	18,975 (8,607)	21,458 (9,733)
Gross engine power	hp (kW)	48.3 (36)	55 (41)	64.4 (48)	64.4 (48)	73.8 (55)	73.8 (55)
Dig depth (dozer down)	ft-in (mm)	13-4 (4,084)	13-4 (4,084)	12-12 (3,694)	14-4 (4,389)	13-6 (4,145)	15-0 (4,572)
Ground-level reach	ft-in (mm)	20-1 (6,126)	21-2 (6,461)	22-6 (6,888)	23-3 (7,102)	23-8 (7,254)	24-0 (7,315)
Dump height	ft-in (mm)	14-7 (4,480)	13-8 (4,206)	16-6 (5,060)	17-8 (5,425)	17-5 (5,334)	18-7 (5,700)
Bucket breakout force	lbf (kN)	9,442 (42)	10,611 (47.2)	12,837 (57.1)	12,837 (57.1)	12,837 (57.1)	16,231 (72.2)



TRACKED EXCAVATORS

JCB LARGE TRACKED EXCAVATORS ARE KNOWN FOR STRENGTH, PERFORMANCE AND PRODUCTIVITY. FROM QUARRIES TO DEMOLITION PROJECTS, HOUSING SITES TO RAIL CONSTRUCTION, JCB DELIVERS A LARGE TRACKED EXCAVATOR MODEL TO MEET EVERY APPLICATION.



<https://forklift-manuals.jimdofree.com>



		JS131	JZ141	JS145	JS160	JS190	220X	JS300	JS330	JS370
Operating weight	lb (kg)	31,499 (14,288)	35,283 (16,004)	32,227 (14,618)	38,665 (17,538)	43,896 (19,911)	52,450 (23,791)	71,161 (32,278)	76,201 (34,564)	81,992 (37,191)
Gross engine power	hp (kW)	74 (55)	74 (55)	109 (81)	125 (93)	125 (93)	173 (129)	241 (180)	281 (210)	281 (210)
Dipper options	ft-in (m)	6-11/8-2/8-10/9-10 (2.1/2.5/2.7/3.0)	6-11/8-2/8-10/9-10 (2.1/2.5/2.7/3.0)	6-11/8-2/8-10/9-10 (2.1/2.5/2.7/3.0)	7-5/8-10/10-0 (2.25/2.7/3.05)	7-5/8-10/10-0 (2.25/2.7/3.05)	7-10/9-10 (2.4/3.0)	8-2/10-2/12-2 (2.5/3.1/3.7)	7-3/8-6/10-6/13-2 (2.21/2.63/3.23/4.03)	7-3/8-6/10-6/13-2 (2.21/2.63/3.23/4.03)
Undercarriage options		LC	LC / HD	LC / HD	LC / NLC	LC / NLC	LC	LC / NLC	LC / NLC	LC / NLC
Machine variants		MONO	MONO	MONO / TAB / LONG REACH	MONO / TAB	MONO / TAB	MONO / TAB / XD / LONG REACH	MONO / TAB	MONO / TAB / XD / ME / LR / HRD	MONO / TAB / XD / ME / LR / HRD
Dipper breakout	lbf (kNm)	16,299 (72.5)	16,793 (74.7)	16,299 (72.5)	19,289 (85.8)	19,289 (85.8)	28,461 (126.6)	38,577 (171.6)	46,625 (207.4)	55,258 (245.8)
Bucket breakout	lbf (kNm)	20,660 (91.9)	20,682 (92)	20,660 (91.9)	26,100 (116.1)	26,100 (116.1)	33,721 (150)	55,595 (247.3)	51,931 (231)	59,754 (265.8)
Pump flow	gpm (lpm)	2 x 34.3 (2 x 130)	2 x 34.3 (2 x 130)	2 x 32.8 (2 x 124)	2 x 43 (2 x 164)	2 x 43 (2 x 164)	2 x 60.2 (2 x 228)	2 x 66 (2 x 250)	2 x 76.9 (2 x 290)	2 x 80.3 (2 x 304)

BACKHOE LOADERS

JCB IS THE GLOBAL LEADER IN BACKHOE LOADERS, AND JCB SETS THE STANDARD FOR OTHERS TO FOLLOW WHEN IT COMES TO BACKHOE POWER, PERFORMANCE AND FEATURES. DESIGNED, BUILT AND TESTED TO EXCEL IN THE MOST DEMANDING JOB SITES, JCB BACKHOE LOADERS COME WITH THE INDUSTRY'S ONLY 5-YEAR / 5,000 HOUR WARRANTY.



<https://forklift-manuals.jimdofree.com>

		3CX COMPACT	3CX	3CX-14	3CX-14 SUPER	3CX-15 SUPER
Operating weight	lb (kg)	13,514 (6,130)	17,196 (7,800)	17,704 (8,030)	18,614 (8,443)	19,090 (8,659)
Gross engine power	hp (kW)	74 (55)	74 (55)	74 (55)	91/109 (68/81)	109 (81)
Dig depth	ft-in (m)	14-2 (4.33)	18-6 (5.63)	18-6 (5.63)	18-6 (5.63)	20-1 (6.12)
Steer mode		4WS	2WS	2WS	2WS	2WS
Loader breakout force	lbf (kgf)	8,285 (3,758)	13,603 (6,170)	13,603 (6,170)	13,603 (6,170)	13,603 (6,170)
Loader bucket capacity	yd ³ (m ³)	0.92 (0.7)	1.4 (1.1)	1.4 (1.1)	1.6 (1.2)	1.6 (1.2)
Dipper breakout force	lbf (kgf)	6,327 (2,870)	7,110 (3,225)	7,110 (3,225)	8,605 (3,903)	8,605 (3,903)
Excavator bucket breakout force	lbf (kgf)	7,363 (3,340)	13,730 (6,228)	13,730 (6,228)	13,730 (6,228)	13,730 (6,228)

		4CX-14 SUPER	4CX-15 SUPER
Operating weight	lb (kg)	19,172 (8,696)	19,648 (8,912)
Gross engine power	hp (kW)	109 (81)	109 (81)
Dig depth	ft-in (m)	18-6 (5.63)	20-1 (6.12)
Steer mode		4WS	4WS
Loader bucket breakout force	lbf (kgf)	13,728 (6,227)	13,728 (6,227)
Loader bucket capacity	yd ³ (m ³)	1.6 (1.2)	1.6 (1.2)
Dipper breakout force	lbf (kgf)	8,605 (3,903)	8,605 (3,903)
Excavator bucket breakout force	lbf (kgf)	13,730 (6,228)	13,730 (6,228)

TOOL CARRIER TELEHANDLERS

JCB INVENTED THE TELESCOPIC HANDLER MORE THAN 40 YEARS AGO AND IS THE WORLD'S BIGGEST SELLING TELEHANDLER BRAND. JCB TOOL CARRIER TELEHANDLERS RANGE FROM COMPACT UNITS TO SOME OF HIGHEST LIFTING, HIGHEST-CAPACITY MACHINES ON THE MARKET. JCB COMPONENTS ENSURE OPTIMAL PERFORMANCE, EFFICIENCY AND RELIABILITY.



		505-20TC	506-23TC	509-23TC	509-45TC	510-55TC	512-26 Industrial	508-66TC
Lift height	ft-in (m)	20-0 (6.0)	23 (7.0)	23 (7.0)	45-2 (13.8)	54-9 (16.7)	26-6 (8.1)	65-7 (20.0)
Lift capacity	lb (kg)	5,500 (2,500)	6,800 (3,100)	9,000 (4,100)	8,800 (4,000)	10,000 (4,535)	12,000 (6,000)	8,800 (4,000)
Lift capacity at full height (on tires)	lb (kg)	3,900 (1,750)	5,200 (2,400)	5,000 (2,250)	9,000 (4,082)	3,000 (1,361)	6,600 (3,000)	1,100 (500)
Lift capacity at full height (on stabilizers)	lb (kg)	3,000 (1,360)	NA	NA	6,600 (3,000)	5,000 (2,269)	NA	3,300 (1,500)
Lift capacity at full reach (on tires)	lb (kg)	1,750 (800)	2,750 (1,250)	3,300 (1,500)	440 (200)	0 (0)	3,800 (1,750)	0 (0)
Lift capacity at full reach (on stabilizers)	lb (kg)	NA	NA	NA	2,750 (1,250)	1,000 (453)	NA	440 (200)
Forward reach	ft-in (m)	11-6 (3.5)	12-1 (3.7)	12-1 (3.7)	31-9 (9.7)	41-5 (12.6)	14-8 (4.47)	52-1 (15.9)
Overall height	ft-in (m)	6-2 (1.9)	8-2 (2.0)	8-2 (2.0)	8-6 (2.6)	8-10 (2.7)	8-6 (2.6)	8-11 (2.7)
Overall width (over tires)	ft-in (m)	6-0 (1.84)	7-3 (2.2)	7-3 (2.2)	7-8 (2.3)	8-0 (2.4)	8-4 (2.5)	8-0 (2.4)
Overall length to front carriage	ft-in (m)	13-1 (4)	16-4 (5.0)	16-4 (5.0)	20-5 (6.2)	20-10 (6.4)	17-3 (5.3)	22-4 (6.8)
Outside turn radius (over tires)	ft-in (m)	12-1 (3.7)	12-2 (3.7)	12-2 (3.7)	12-3 (3.7)	13-5 (4.1)	13-5 (4.1)	13-5 (4.1)
Weight	lb (kg)	12,100 (5,490)	15,565 (7,060)	15,565 (7,060)	23,986 (10,880)	27,494 (12,470)	24,340 (11,040)	28,627 (12,985)
Tires		12 x 16.5	15.5/80-24	15.5/80-24	15.5/80-24	17.5-25	480/80 R26	17.5-25
Gross engine power (standard)	hp (kW)	74 (55)	74 (55)	74 (55)	109 (81)	74 (55)	125 (93)	74 (55)
Gross engine power (optional)	hp (kW)		109 (81)	109 (81)		109 (81)		

LIFT & PLACE TELEHANDLERS

JCB INVENTED THE TELESCOPIC HANDLER MORE THAN 40 YEARS AGO AND IS THE WORLD'S BIGGEST SELLING TELEHANDLER BRAND. JCB LIFT & PLACE TELEHANDLERS DELIVER INDUSTRY-LEADING PERFORMANCE, VERSATILITY AND OPERATOR COMFORT, AND COMMAND THE INDUSTRY'S HIGHEST RESALE VALUES.



<https://forklift-manuals.jimdofree.com>

		506-36	507-42	509-42	510-42	510-56	512-56	514-56
Lift height	ft-in (m)	36-4 (11.1)	42-0 (12.8)	42-0 (12.8)	42-0 (12.8)	56-0 (17.1)	56-0 (17.1)	56-0 (17.1)
Lift capacity	lb (kg)	6,000 (2,722)	7,000 (3,175)	9,000 (4,084)	10,000 (4,537)	10,000 (4,537)	12,000 (5,444)	14,000 (6,350)
Lift capacity at full height (on tires)	lb (kg)	6,000 (2,722)	6,000 (2,722)	6,000 (2,722)	6,000 (2,722)	3,000 (1,361)	4,000 (1,814)	4,000 (1,814)
Lift capacity at full height (on stabilizers)	lb (kg)	NA	NA	NA	NA	4,000 (1,814)	5,000 (2,268)	5,000 (2,268)
Lift capacity at full reach (on tires)	lb (kg)	1,800 (816)	1,600 (725)	1,800 (816)	2,500 (1,133)	300 (136)	300 (136)	500 (227)
Lift capacity at full reach (on stabilizers)	lb (kg)	NA	NA	NA	NA	3,000 (1,360)	3,500 (1,587)	3,500 (1,587)
Forward reach	ft-in (m)	24-0 (7.3)	28-0 (8.5)	28-0 (8.5)	28-0 (8.5)	42-0 (12.8)	42-0 (12.8)	42-0 (12.8)
Overall height	ft-in (m)	8-3 (2.5)	8-3 (2.5)	8-3 (2.5)	8-3 (2.5)	8-10 (2.7)	8-10 (2.7)	8-11 (2.7)
Overall width (over tires)	ft-in (m)	7-10 (2.4)	7-10 (2.4)	7-10 (2.4)	7-10 (2.4)	8-1 (2.5)	8-1 (2.5)	8-1 (2.5)
Overall length to front carriage	ft-in (m)	17-1 (5.2)	17-8 (5.4)	17-0 (5.2)	17-8 (5.4)	21-7 (6.6)	21-7 (6.6)	22-4 (6.8)
Outside turn radius (over tires)	ft-in (m)	14-6 (4.4)	13-9 (4.2)	13-9 (4.2)	21-3 (6.5)	14-1 (4.3)	14-1 (4.3)	14-4 (4.4)
Weight	lb (kg)	20,270 (9,193)	21,300 (9,660)	22,430 (10,172)	23,858 (10,822)	29,900 (13,560)	30,635 (13,895)	32,143 (14,580)
Tires		13.00-24	14.00-24	14.00-24	14.00-24	17.5-25	17.5-25	17.5-25
Gross engine power (standard)	hp (kW)	74 (55)	74 (55)	74 (55)	74 (55)	74 (55)	74 (55)	109 (81)
Gross engine power (optional)	hp (kW)			109 (81)	109 (81)	109 (81)	109 (81)	

SKID STEER LOADERS AND COMPACT TRACK LOADERS

JCB REVOLUTIONIZED THE SKID STEER LOADER AND COMPACT TRACK LOADER MARKET WITH THE SINGLE-ARM JCB POWERBOOM™ AND SIDE-DOOR ENTRY. THE RESULT IS THE WORLD'S SAFEST SKID STEER, WITH A SIGNIFICANTLY LARGER CAB, 60 PERCENT BETTER VISIBILITY AND 21 PERCENT INCREASE IN PRODUCTIVITY.



<https://forklift-manuals.jimdofree.com>

SKID STEERS		155	175	210	215	250	270	300	330
Lift path		Radial	Vertical	Radial	Vertical	Radial	Vertical	Vertical	Vertical
Operating weight (no counterweight)	lb SAE (kg)	6,515 (2,955)	6,818 (3,093)	6,885 (3,123)	7,253 (3,290)	8,214 (3,726)	8,680 (3,937)	9,288 (4,213)	9,736 (4,416)
Gross engine power	hp (kW)	56 (42)	56 (42)	74 (55)	74 (55)	74 (55)	74 (55)	74 (55)	74 (55)
Rated operating capacity (ROC) 50%	lb SAE (kg)	1,550 (703)	1,753 (795)	2,114 (959)	2,112 (958)	2,526 (1,146)	2,723 (1,235)	3,186 (1,445)	3,296 (1,495)
Tipping load (no counterweight)	lb (kg)	3,100 (1,406)	3,505 (1,590)	4,228 (1,918)	4,222 (1,915)	5,055 (2,293)	5,448 (2,471)	6,369 (2,889)	6,590 (2,989)
Auxiliary flow - standard/option	gpm (lpm)	18/26 (70/100)	18/26 (70/100)	18/30 (70/115)	18/30 (70/115)	24/33 (90/125)	24/33 (90/125)	24/33 (90/125)	24/33 (90/125)
Hinge pin height	ft-in (m)	9-10 (3.00)	9-10 (3.00)	9-10 (3.00)	9-10 (3.00)	10-6 (3.2)	10-6 (3.2)	10-6 (3.2)	10-7 (3.225)

COMPACT TRACK LOADERS		150T	210T	215T	250T	270T	300T	320T	325T
Lift path		Radial	Radial	Vertical	Radial	Vertical	Vertical	Vertical	Vertical
Operating weight (no counterweight)	lb SAE (kg)	8,137 (3,691)	8,865 (4,021)	9,098 (4,127)	10,622 (4,818)	11,003 (4,991)	11,219 (5,089)	11,570 (5,248)	12,364 (5,608)
Gross engine power	hp (kW)	56 (42)	74 (55)	74 (55)	74 (55)	74 (55)	74 (55)	74 (55)	74 (55)
Rated operating capacity (ROC) 35%	lb SAE (kg)	1,500 (680.4)	1,855 (841)	2,105 (955)	2,526 (1,146)	2,723 (1,235)	3,000 (1,361)	3,201 (1,452)	3,201 (1,452)
Tipping load (no counterweight)	lb (kg)	4,284 (1,943)	5,298 (2,403)	6,016 (2,729)	7,721 (3,502)	7,990 (3,624)	8,627 (3,913)	9,145 (4,148)	9,145 (4,148)
Auxiliary flow - standard/option	gpm (lpm)	18/26 (70/100)	18/30 (70/115)	18/30 (70/115)	24/33 (90/125)	24/33 (90/125)	24/33 (90/125)	24/33 (90/125)	24/33 (90/125)
Hinge pin height	ft-in (m)	9-11 (3.02)	9-11 (3.02)	9-11 (3.02)	10-5 (3.18)	10-5 (3.18)	10-5 (3.18)	10-5 (3.18)	10-5 (3.18)

TELESKID

THE NEW JCB TELESKID IS THE FIRST SKID STEER AND COMPACT TRACK LOADER WITH A TELESCOPIC BOOM, MAKING IT THE MOST VERSATILE MACHINE YOU'VE EVER SEEN. TELESKID ALLOWS YOU TO LIFT HIGHER, REACH FURTHER AND DIG DEEPER THAN ANY OTHER SKID STEER ON THE MARKET, AND ACCESS AREAS YOU WOULDN'T HAVE THOUGHT POSSIBLE...UNTIL NOW.



<https://forklift-manuals.jimdofree.com>



		3TS-8W	3TS-8T
Gross engine power	hp (kW)	74 (55)	74 (55)
Rated operating capacity (ROC) 35% - retracted	lb (kg)	3,208 (1,455)	3,695 (1,676)
Rated operating capacity (ROC) 35% - extended	lb (kg)	1,347 (611)	1,614 (732)
Operating weight	lb (kg)	9,859 (4,472)	12,615 (5,722)
Lift path		Radial and Vertical	Radial and Vertical
Load height	ft-in (m)	12-3 (3.7)	12-5 (3.8)
Reach	ft-in (m)	7-4 (2.25)	7-4 (2.25)

ARTICULATED TELESCOPIC HANDLERS

JCB ARTICULATED TELESCOPIC HANDLERS ARE HIGHLY MANEUVERABLE AND IDEALLY SUITED TO MATERIAL HANDLING APPLICATIONS. POWERFUL AND VERSATILE, THESE MACHINES ARE DESIGNED SPECIFICALLY TO BOOST PRODUCTIVITY WHERE SPACE IS LIMITED.



		TM220	TM320
Operating weight	lb (kg)	14,319 (6,495)	17,151 (7,780)
Gross engine power	hp (kW)	74 (55)	125 (93)
Torque	lbf (Nm)	221 (300)	406 (550)
Tipping load	lb (kg)	5,436 (2,465)	8,644 (3,921)
Lift capacity	lb (kg)	4,410 (2,000)	6,390 (2,904)
Pump flow	gpm (lpm)	23.5 (89)	37 (140)
Travel speed	mph (km/h)	25 (40)	25 (40)

<https://forklift-manuals.jimdofree.com>

COMPACT WHEEL LOADERS

FOR WORK IN CONFINED SPACES, JCB 407 AND 409 WHEEL LOADERS ARE COMPACT, MANEUVERABLE AND VERSATILE. BOTH MODELS FEATURE HYDROSTATIC TRANSMISSION, ALL-WHEEL DRIVE, PIVOT STEER, EXCELLENT GROUND CLEARANCE AND LOW HEIGHT OVER CAB.



		407	409
Operating weight	lb (kg)	11,162 (5,063)	13,067 (5,927)
Gross engine power	hp (kW)	64 (48)	74 (55)
Standard bucket capacity	yd ³ (m ³)	1.0 (0.76)	1.3 (1.0)
Full-turn tipping load	lb (kg)	7,333 (3,326)	8,042 (3,648)
Payload 50% (bucket)	lb (kg)	3,667 (1,663)	4,021 (1,824)
Payload 80% (forks)*	lb (kg)	4,722 (2,142)	5,216 (2,366)
Breakout force	lbf (kN)	960 (4.27)	1,233 (5.49)
Hinge height	ft-in (m)	10-3 (3.12)	10-11 (3.32)
Auxiliary flow - standard/option	gpm (lpm)	15.8/22.9 (60/87)	21.9/29.0 (83/110)
Travel speed - standard/option	mph (km/h)	12.4/21.7 (20/35)	12.4/24.5 (20/40)

WHEEL LOADERS

JCB WHEEL LOADERS ARE POWERFUL, EASY TO MAINTAIN AND DESIGNED TO MOVE MORE MATERIAL WITH GREATER EFFICIENCY. WHEN YOU NEED A WHEEL LOADER TO GET THE JOB DONE, DEPEND ON JCB.



		411 HT	417 HT	417 HT HL	417 HT SHL	427 HT	427 HT HL	427 ZX
Operating weight	lb (kg)	19,689 (8,931)	21,164 (9,600)	21,308 (9,665)	22,498 (10,205)	30,770 (13,957)	30,710 (13,930)	30,708 (13,929)
Gross engine power	hp (kW)	109 (81)	125 (93)	125 (93)	125 (93)	179 (133)	179 (133)	179 (133)
Standard bucket capacity	yd ³ (m ³)	1.8 (1.4)	2.0 (1.6)	1.8 (1.4)	1.8 (1.4)	3.1 (2.4)	2.7 (2.1)	3.1 (2.4)
Full-turn tipping load	lb (kg)	11,424 (5,182)	12,714 (5,767)	12,004 (5,445)	8,757 (3,972)	18,640 (8,455)	16,168 (7,334)	18,966 (8,603)
Payload 50% (bucket)	lb (kg)	5,715 (2,591)	6,446 (2,924)	6,003 (2,723)	4,378 (1,986)	9,321 (4,228)	8,084 (3,667)	9,482 (4,301)
Payload 80% (forks)*	lb (kg)	7,405 (3,360)	8,206 (3,722)	7,676 (3,482)	5,798 (2,630)	16,909 (7,670)	15,106 (6,852)	16,645 (7,550)
Breakout force	lbf (kN)	14,006 (62.3)	13,466 (59.9)	14,590 (64.9)	14,590 (64.9)	23,829 (106)	25,403 (113)	29,000 (129)
Hinge height	ft-in (m)	11-8 (3.569)	11-8 (3.566)	12-11 (3.946)	14-5 (4.411)	12-8 (3,876)	14-1 (4,306)	12-9 (3,904)
Auxiliary flow	gpm (lpm)	19 (72)	42 (160)	42 (160)	42 (160)	30.9 (117)	30.9 (117)	30.9 (117)
Travel speed - standard/option	mph (km/h)	25 (40)	25 (40)	25 (40)	25 (40)	23.6/24.8 (38/40)	23.6/24.8 (38/40)	23.6/24.8 (38/40)

		437 HT	437 HT HL	437 HT SHL	437 ZX	457 HT	457 HT SHL	457 ZX (HD CW)
Operating weight	lb (kg)	33,358 (15,131)	34,145 (15,488)	35,137 (15,938)	34,518 (15,657)	45,270 (20,534)	47,174 (21,398)	45,300 (20,548)
Gross engine power	hp (kW)	183 (136)	183 (136)	183 (136)	183 (136)	258 (193)	258 (193)	258 (193)
Standard bucket capacity	yd ³ (m ³)	3.5 (2.7)	3.1 (2.4)	3.1 (2.4)	3.5 (2.7)	4.6 (3.5)	4.3 (3.3)	4.6 (3.5)
Full-turn tipping load	lb (kg)	20,007 (8,495)	16,554 (6,929)	12,236 (4,970)	19,661 (8,338)	27,566 (12,504)	17,833 (8,089)	32,214 (14,612)
Payload 50% (bucket)	lb (kg)	10,005 (4,248)	8,276 (3,464)	6,118 (2,485)	9,830 (4,169)	13,783 (6,252)	8,917 (4,045)	16,543 (7,504)
Payload 80% (forks)*	lb (kg)	17,919 (8,128)	15,185 (6,888)	12,139 (5,506)	18,570 (8,423)	17,637 (8,000)	13,025 (5,908)	18,424 (8,357)
Breakout force	lbf (kN)	27,426 (122)	29,449 (131)	30,574 (136)	32,372 (144)	29,225 (130)	30,799 (137)	34,620 (154)
Hinge height	ft-in (m)	13-2 (4,021)	15-4 (4,675)	17-2 (5,242)	13-2 (4,021)	14-1 (4,307)	17-3 (5,273)	13-5 (4,110)
Auxiliary flow	gpm (lpm)	30.9 (117)	30.9 (117)	30.9 (117)	30.9 (117)	39 (150)	39 (150)	39 (150)
Travel speed - standard/option	mph (km/h)	23.6/24.8 (38/40)	23.6/24.8 (38/40)	23.6/24.8 (38/40)	23.6/24.8 (38/40)	23.6/24.8 (38/40)	22.4/25 (36.1/40.5)	22.4/25 (36.1/40.5)

* At 100% of gravity dist. @ 19.0 in (480 mm) Bredt. 80% of TTT. Based on ISO 9001, ISO 14001, ISO 45001, CE, OSHA, and PSE. © 2018 Bobcat Company

ELECTRIC SCISSORS

THE JCB RANGE OF ACCESS ELECTRIC SCISSOR LIFTS IS DESIGNED TO A HIGHER STANDARD, TO MEET THE NEEDS OF RENTAL COMPANIES AND CONTRACTORS. NINE MODELS ARE AVAILABLE, WITH PLATFORM HEIGHTS FROM 15 TO 45 FEET, WITH EVERY MACHINE OPTIMIZED FOR SAFETY, RELIABILITY AND PERFORMANCE.



		SI530E	SI930E	S2032E	S2046E	S2632E	S2646E	S3246E	S4046E	S4550E
Platform height	ft-in (m)	15-1 (4.6)	19-0 (5.8)	20-8 (6.3)	20-8 (6.3)	26-6 (8.1)	26-6 (8.1)	32-9 (10)	39-0 (11.9)	45-3 (13.8)
Load capacity	lb (kg)	615 (280)	505 (230)	840 (380)	1,210 (550)	550 (250)	990 (450)	705 (320)	705 (320)	500 (227)
Platform occupants (outdoor)		1	1	1	2	-	2	1	1	-
Overall length (stowed)	ft-in (m)	5-10 (1.78)	5-10 (1.78)	7-10 (2.39)	7-10 (2.39)	7-10 (2.39)	7-10 (2.39)	7-10 (2.39)	7-10 (2.39)	9-1 (2.76)
Overall width (stowed)	ft-in (m)	2-6 (0.76)	2-6 (0.76)	2-8 (0.81)	3-9 (1.15)	2-8 (0.81)	3-9 (1.15)	3-9 (1.15)	3-9 (1.15)	4-1 (1.25)
Overall height (stowed, guardrail folded)	ft-in (m)	6-0 (1.84)	6-1 (1.86)	6-0 (1.83)	6-0 (1.83)	6-5 (1.96)	6-5 (1.96)	6-1 (1.86)	6-6 (1.98)	7-3 (2.20)
Overall height (stowed, guardrail unfolded)	ft-in (m)	6-11 (2.11)	6-11 (2.12)	7-3 (2.22)	7-3 (2.22)	7-8 (2.35)	7-8 (2.35)	8-2 (2.48)	8-6 (2.60)	8-6 (2.60)
Overall weight	lb (kg)	2,932 (1,330)	3,364 (1,526)	4,044 (1,834)	4,705 (2,134)	4,546 (1,972)	4,348 (2,528)	5,834 (2,646)	6,606 (2,996)	7,422 (3,366)



TELETRUKS

INVENTED BY JCB, THE TELETRUCK DOES THE WORK OF A CONVENTIONAL FORKLIFT BUT WITH A TELESCOPIC BOOM INSTEAD OF A VERTICAL MAST, ENABLING FASTER CYCLE TIMES, BETTER UTILIZATION OF YARD SPACE AND IMPROVED ONSITE SAFETY.



<https://forklift-manuals.jimdofree.com>



		TLT30HL	TLT35	TLT35D 4x4
Lift height	ft-in (m)	16-11 (5.2)	14-5 (4.4)	14-3 (4.3)
Lift capacity	lb (kg)	6,000 (2,722)	7,000 (3,175)	7,000 (3,175)
Lift capacity at full height	lb (kg)	6,000 (2,722)	7,000 (3,175)	7,000 (3,175)
Lift capacity at full reach	lb (kg)	3,000 (1,361)	3,250 (1,474)	3,250 (1,474)
Forward reach	ft-in (m)	10-11 (3.3)	7-11 (2.4)	8-0 (2.4)
Overall height	ft-in (m)	7-3 (2.2)	7-3 (2.2)	7-7 (2.3)
Overall width (over tires)	ft-in (m)	4-2 (1.3)	4-2 (1.3)	4-7 (1.4)
Overall length to front carriage	ft-in (m)	11-1 (3.4)	9-10 (3.0)	10-6 (3.2)
Outside turn radius (over tires)	ft-in (m)	9-6 (2.9)	9-6 (2.9)	11-6 (3.5)
Weight	lb (kg)	11,861 (5,380)	11,220 (5,089)	12,125 (5,500)
Tires - front		27x10	27x10	27x10
Tires - rear		23x9	23x9	27x10
Gross engine power	hp (kW)	62 (46)	62 (46)	62 (46)

ROUGH TERRAIN FORKLIFTS

JCB ROUGH TERRAIN FORKLIFTS ARE THE RELIABLE AND VERSATILE SOLUTION FOR VIRTUALLY ALL REHANDLING APPLICATIONS, FROM DOCKS TO YARDS, FROM SPECIAL EVENTS TO CONSTRUCTION AND FORESTRY. JCB ROUGH TERRAIN FORKLIFTS ARE AVAILABLE IN A RANGE OF OPERATING WEIGHTS, CAPACITIES AND DIMENSIONS.



<https://forklift-manuals.jimdofree.com>

		930	940	950
Lift capacity	lb (kg)	6,000 (2,722)	8,000 (3,629)	10,000 (4,536)
Overall lowered height with 22 ft Clearview Mast	ft-in (m)	10-7 (3.2)	10-7 (3.2)	10-7 (3.2)
Overall raised height with 22 ft Clearview Mast	ft-in (m)	25-2 (7.7)	25-2 (7.7)	25-2 (7.7)
Height of mast lift with 22 ft Clearview Mast	ft-in (m)	22-0 (6.7)	22-0 (6.7)	22-0 (6.7)
Capacity at full height with 22 ft Clearview Mast	lb (kg)	2,500 (1,134)	3,500 (1,588)	6,500 (2,948)
Travel speed	mph (km/h)	18 (29)	18 (29)	18 (29)
Mast shift	in (cm)	4 (10)	4 (10)	4 (10)
Overall height	ft-in (m)	8-4 (2.5)	8-4 (2.5)	8-4 (2.5)
Overall width (over tires)	ft-in (m)	7-2 (2.2)	7-2 (2.2)	7-2 (2.2)
Overall length to front carriage	ft-in (m)	11-7 (3.5)	11-7 (3.5)	11-9 (3.6)
Mast tilt forwards	degrees	18	18	18
Mast tilt backwards	degrees	10	10	10
Weight with 22 ft Clearview Mast	lb (kg)	14,495 (6,575)	15,750 (7,144)	17,295 (7,845)
Outside 2WD	ft-in (m)	14-4 (4.4)	14-7.2 (4.5)	14-7.2 (4.5)
Outside 4WD	ft-in (m)	14-3 (4.3)	16-2 (4.9)	16-2 (4.9)
Tires		15.5-25	15.5-25	15.5-25
Gross engine power	hp (kW)	74 (55)	74 (55)	74 (55)

LIGHT EQUIPMENT

THE RANGE OF JCB LIGHT EQUIPMENT INCLUDES EVERYTHING FROM POWERPACKS TO HANDHELD BREAKERS, PUMPS, VIBRATORY RAMMERS AND COMPACTION PLATES. EACH PRODUCT FEATURES JCB'S UNRIVALED QUALITY, INNOVATION AND RELIABILITY.



<https://forklift-manuals.jimdofree.com>

POWERPACKS		MICRO	COMPACT	BEAVER	TROJAN (5.3 GAL)	TROJAN (8 GAL)	MULTIFLOW
Engine		Honda GX160	Honda GX160	Honda GX240	Honda GX390	Honda GX390	Briggs and Stratton
Fuel		Gas	Gas	Gas	Gas	Gas	Gas
Power	hp (kW)	5.5 (4)	5.5 (4)	6 (4.5)	9.7 (7.2)	9.7 (7.2)	13.4 (10)
Hydraulic flow	gpm (lpm)	0-5 (0-20)	0-5 (0-20)	0-5 (0-20)	0-5 (0-20)	0-7.9 (0-30)	0-5/7.9/10.5 (0-40)
Weight	lb (kg)	100 (45)	126 (57)	146 (66)	205 (93)	205 (93)	225 (102)
Hose length	ft-in (m)	16-5 (5)	23 (7)	23 (7)	23 (7)	23 (7)	23 (7)

HAND HELD BREAKERS		D-PICK	T-PICK	HM22	HM25	HM25 LV	HM29
Weight	lb (kg)	33 (15)	33 (15)	46 (21)	46 (21)	60 (27)	64 (29)
Hydraulic flow	gpm (lpm)	4.0-5.8 (15-22)	3-5 (11-19)	4.0-5.8 (15-22)	4.8-5.8 (18-22)	4.8-5.8 (18-22)	4.8-5.8/7.4-8.4 (18-32)
Vibration (BS8622-5)	yd/s ² (m/s ²)	6.5 (6)	8.2 (7.5)	3.7 (3.4)	4.3 (4)	1.75 (1.6)	5.5 (5)
Sound power level	dB Lwa	106	106	106	106	108	108

PUMPS		TRASH PUMPS		SUBMERSIBLE PUMPS	
Weight	lb (kg)	71 (32)	71 (32)	18 (8)	19 (9)
Hydraulic flow	gpm (lpm)	0-5.3 (0-20)	0-7.9 (0-30)	0-5.8 (0-22)	0-8.45 (0-32)
Discharge port BSP Male	in (mm)	4 (101)	4 (101)	2 (51)	2 (51)
Discharge	gpm (lpm)	570 (2,150)	697 (2,635)	185 (700)	217 (820)



<https://forklift-manuals.jimdofree.com>

TOOLS		EARTH DRILL	DISC CUTTER	DIAMOND CORE DRILL	REVERSIBLE DRILL	ROTARY IMPACT DRILL	IMPACT WRENCH
Weight	lb (kg)	34 (15)	22.5 (10)	18 (8)	6 (3)	9 (4)	12 (5)
Hydraulic flow	gpm (lpm)	4-6.6 (15-25)	4-4.6 (16-17)	4-6.5 (15-25)	4-8 (15-30)	5-9 (19-34)	4-12 (15-45)

VIBRATORY RAMMER		VMR60	FORWARD VIBRATORY PLATES		FPI030	FPI540	FPI550
Engine		Honda GX100	Engine		Honda GX100	Honda GX160	Honda GX160
Performance DIN 6,271	hp (kW)	3.4 (2.5)	Power	hp (kW)	2.8 (2)	4.8 (3.5)	4.8 (3.5)
Operating weight (CECE)	lb (kg)	132 (60)	Operating weight	lb (kg)	143-165 (64-74)	201-243 (91-110)	220-262 (100-118)
Working width	in (mm)	14.5 (368)	Working width	in (mm)	11.8 (300)	15.7 (400)	19.7 (500)
Blows/minute		740	Frequency	Hz	100	100	100
Tamping force	lbf (kn)	3,147 (14)	Centrifugal force	lbf (kn)	2,248 (10)	3,372 (15)	3,372 (15)

REVERSIBLE VIBRATORY PLATES		VMP8
Engine		Honda GX120
Power	hp (kW)	3.9 (3)
Operating weight	lb (kg)	176 (80)
Working width	in (mm)	13 x 23 (330 x 584)
Frequency	Hz	100
Centrifugal force	lbf (kn)	3,597 (16)
Starter recoil		Recoil


ATTACHMENTS

GENUINE JCB ATTACHMENTS ARE PERFECTLY MATCHED TO JCB MACHINES AND BACKED BY THE GLOBAL JCB SERVICE TEAM. FROM BUCKETS TO SPECIALIZED PRODUCTS FOR A WIDE RANGE OF APPLICATIONS, JCB HAS THE RIGHT ATTACHMENT TO GET THE JOB DONE.




<https://forklift-manuals.jimdofree.com>

EXCAVATOR BUCKETS




LOADER BUCKETS




HAMMERS




QUICK COUPLERS




COMPACTORS




PLANERS




CRANE HOOKS




FORKS & FRAMES



EXTENSION JIBS



UPGRADE KITS




HANDHELD BREAKERS



HYDRAULIC TOOLS



SWEEPER COLLECTORS & BROOMS




WATER PUMPS



VIBRATORY RAMMERS




FORWARD VIBRATORY PLATES



REVERSIBLE VIBRATORY PLATES




SNOW ATTACHMENTS




MULTIPROCESSORS




HYDRAULIC POWERPACKS




EARTH DRILLS/AUGERS




FORESTRY EQUIPMENT



WASTE BUCKETS



SELECTOR GRABS



LIVELINK, WORK SMARTER

LiveLink keeps track of each machine's efficiency, so you get the best value for money.



- Manage your fleet anywhere
- Drive down cost
- Improve productivity
- Fuel level and consumption*
- Customized reports by day / week / month

**For machines with electronic engine management system only*

LiveLink sends service alerts and diagnostic warnings to ensure your machine's maximum uptime.



- Machine health alerts
- Machine service alerts
- Accurate hours recorded
- Detailed machine history
- Maintenance planning

LiveLink reports machine's exact location, movement and activity offering greater protection against theft.



- Pinpoint machine location
- 24/7 update on your phone/tablet
- Real-time curfew alerts
- Real-time geofence alerts
- Back-up battery
- Tow-away alert



Peace of Mind

Machine Servicing Agreement



<https://forklift-manuals.jimdofree.com>

VALUE ADDED

WHATEVER YOU NEED AND WHEREVER YOU ARE, JCB'S DEPENDABLE NORTH AMERICAN DEALER NETWORK IS HERE TO MAKE SURE YOUR MACHINERY PERFORMS TO ITS FULL POTENTIAL.



1

JCB Technical Support Service provides instant access to factory expertise, day or night.

JCB's Finance and Insurance teams are always on hand to provide fast, flexible, competitive quotes.

The global network of JCB Parts Centers is a model of efficiency. With 16 regional bases, JCB can deliver around 95 percent of all parts anywhere in the world within 24 hours. JCB parts are designed to work in perfect harmony with your machine for optimum performance and productivity.



2

JCB Yellow Shield offers comprehensive extended warranties, as well as service-only or repair and maintenance contracts. JCB maintenance teams offer competitive labor rates and no-obligation quotes.



Note: JCB LIVELINK and JCB ASSETCARE may not be available in your region, so please check with your local dealer.



3



- Manufacturing Facilities
- Dealers
- Parts Distribution Centers



ONE COMPANY, MORE THAN 300 MACHINES.

Your nearest JCB dealer

NORTH AMERICA | CONSTRUCTION RANGE

JCB North America
 2000 Bamford Blvd., Pooler, Georgia, 31322 Tel: (912) 447-2000
 Download the very latest information on this product range at www.jcb.com

JCB inc. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any other means, electronic, mechanical, photocopying or otherwise, without prior permission from JCB inc. All references in this publication to operating weights, sizes, capacities and other performance measurements are provided for guidance only and may vary dependent upon the use and specification of machine. They should not therefore be relied upon in relation to suitability for a particular application. Advice and advice on safety is sought from your JCB Dealer. JCB reserves the right to change specifications without notice. Illustrations and specifications shown may include optional equipment and accessories. The JCB logo is a registered trademark of JCB Bamford, UK and is used here by permission.

<https://forklift-manuals.jimdo.fr/en/>

99 9/6006 7/18 en US Issue 1 | DW SA 45/3

www.jcb.com | [/JCBNA](https://www.facebook.com/jcbna) | [/JCBNA](https://www.instagram.com/jcbna) | [/JCBNA](https://www.linkedin.com/company/jcbna)

