OUR SPECIALITY PROMOTE YOUR CAREER

我们的专业,推动您的事业





https://forklift-manuals.jimdofree.com



Company Profile

Fujian SouthChina Heavy Machinery Manufacture Co., Ltd. (SOCMA) is a modern, high-tech company that integrates development, design, production, marketing, and service in the manufacturing of our large-tonnage diesel forklift truck, telescopic lift truck, telescopic crane loader, wheel loader, and other products. Our company is located in Quanzhou City, in close proximity to the Western Taiwan Straits Economic Zone, where we have easy access to a booming economy and many forms of convenient transportation.

Our forklift truck, telescopic loader etc. are primarily used in the stone, steel, and leasing industries in quarries, docks, railroad stations, timber yards, and industrial and mining companies for lifting, handling, transportation, and other applications. We are ISO9001 approved, due to the efforts of our innovative management team and R&D personnel, as well as our advanced technology.

Customer satisfaction is our ultimate goal at SOCMA. We achieve this by providing quality products and attentive service. Our strict quality control and attention to detail is evident in the entire manufacturing process, from incoming materials, through each stage of production, to the final product. We guarantee the high performance and quality of our products, and our efficient staff is ready to assist you.

The staff at SOCMA continually strives to provide high quality products and professional service for our worldwide customers.



SPECIALIZED IN HEAVY DUTY FORKLIFT

























Advantages:

Advanced design philosophy: through scientific finite element analysis, kinematics and dynamics simulation analysis, base on the supporting of accurate data for the design, to ensure that reasonable door frame and chassis systems structure, excellent performance, stable and reliable operation of the machine.

Advanced manufacturing processes: frame uses GMAW welding, 100% non-damage detection for each key soldering, can withstand rigorous test, wholistic processing for the overall frame, high precision and very good bearing performance. Cost performance: in the premise to ensure the stability and reliablibity of quality, the products are with higher cost performance in the industry.

After-sale service: our company has one professional maintenance service team, including practiced field engineers and senior technician, who can provide timely technical guide and solution for problems

Product Quality: in order to create brand on our early stage, enhancecorporate recognition and establish a corporate image, We follow the market and the user's awe, attention to detail, continuous improvement, diligently pursue excellence.

12-15 tonnage



Strong Lifting And Cross-Country Performance Advanced Design Philosophy

5-20 tonnag

High Cost Performance, High Rate Of Return 3D finite element analysis



20-30 tonnage





Stable and Reliable Damping Luxury Cab


30-40 tonnag


Excellent Operating Performance Exquisite workmanship &firm box-type frame





























HNF-120

HNF-150 HNF-160

HNF-200

HNF-250

HNF-300 HNF-350













Configuration	Model			CPCB128	CPCD150	CPCB160	CPCD200	CPCB250	CPCB300	CPCB350
				HNF-120	HNF-150	HNF-160	HNF-200	HNF-250	HNF-300	HNF-350
Performance	Rated load		kg	12000	15000	16000	20000	25000	30000	35000
	Load center		mm	600	600	600	900	1250	1250	1250
	Free lift		mm	230	180	180	180	180	180	180
	Mast tilt angle (front/rear)		0	6/12	6/12	6/12	6/12	6/12	6/12	6/12
	Overall dimensions	A Length	mm	6220	7645	7645	8340	9190	9690	9700
		B Width	mm	2200	2750	2750	3050	3050	3200	3320
		C Height	mm	3100	3625	3625	3860	3860	4250	4310
		Mast lifting height	mm	3000	3500	3500	3500	3500	3500	3500
	Fork size (L*W*H)		mm	1520X170X80	1800X180X90	1800X180X90	2000X260X100	2440X280X110	2440X320X110	2440X340X125
	Min. turning radius		mm	4200	5800	5800	6250	6700	7260	7260
	Max. travel speed (with load)		Km/h	30	28	28	25	28	28	28
	Lifting speed (with load)		mm/s	290	300	300	180	180	260	260
	Gradeability (with load)		%	20	20	20	20	20	20	20
	Weight		Kg	15500	22000	23000	28000	32000	39500	43000
Tyre	Front			9.00-20-14PR	4X12.00-24/18PR	4X12.00-24/18PR	4X14.00-24/24PR	4X14.00-24/28PR	4X14.00-24/28PR	4X16.00-25/32PI
	Rear			9.00-20-14PR	2X12.00-20/18PR	2X12.00-20/18PR	2X14.00-24/24PR	2X14.00-24/28PR	2X14.00-24/28PR	2X16.00-25/32PI
	Wheel tread	Front	mm	1600	2060	2060	2200	2200	2490	2810
		Rear	mm	1700	2330	2330	2390	2390	2450	2450
	D Wheelbase		mm	3200	3800	3800	4000	4400	4800	4800
	Min. ground clearance		mm	250	265	250	250	250	350	350
Engine	Model			6BT5.9-C130	6BTAA5.9-C190	6BTAA5.9-C190	6CTA8.3-C215	6CTA8.3-C240	6CTAA8.3-C260	6CTAA8.3-C260
	Rated power/rotate speed		KW/r.pm	97/2200	142/2200	142/2200	160/2200	179/2200	191/2200	191/2200
	Max. torque/rotate speed		N.m/r.pm	560/1500	800/1500	800/1500	908/1500	1029/1500	1025/1400	1135/1500

Main Parts And Characters

Engine



- Low fuel consumption, high-quality turbo-charged engine.
- Satisfactory power performance, large tarque reserve.

Tyre rims



- Sino-US joint brand, wear resistant and stab high strength tyre.
- No spoke rims, safe and reliable when under heavy load.

Brake system



- O Adopt the products from professional manufacture.
- O Use disc brake, fast heat emission, light weight, simple structure, and convenient adjustment.
- Especially in the situation of high load, good high temperature resistant performance, stable braking effect.

Cab



- Rupture membrane, explosion proof, heat insulation, prevent glare, sound insulation.
- Damping luxury cab with sunroof, wide view and comfortable seats, flexible control.
- With warm and cooling A/C and reverse monitor.

Transmission



 Hang zhou planetary gearbax, easy maintenance, economic, accessories versatlity, and has good driving performance and traction.

Fork



- O Cascade Fork
- Higher Intensity, more wear-resistant, can be multiplied and increased life expectancy.

Control system



 Pilot valve control device to make the work efficiency and reduce drivers' labor intensity.

Fork Positioner



- Standard equipped with hydraulic fork positioner, easily to operate.
- Can reduce labor intensity and improve working efficiency.

Hydraulic system



O Double pump confluence, small system flow, low power consumption, reliable performance, excellent operating performance.

Drive axle



- Extra Strength drive axia. High intensity overload, planetary hub reduction,
- High strength axie case, large load capacity, excellent stability and reliability

Electrical Equipment



- O Wire and sheath use of flame retardant materials.
- Adopt high-quality domestic electrical components, reliable and durable.
- Equipped with maintenance free high—grade Johnson battery, reliable and steady work.



用心 细心 专业 专注 Attentive & Professional





福建华南重工机械制造有限公司

地址:福建省泉州市台商投资区

国内销售: 0595-27393198 27393199 传真: 0595-27393200

創箱: office@socmachinery.com

国际销售: 0592-5650603 传真: 0592-5650876

客服热线: 400-0068-123

FUJIAN SOUTHCHINA HEAVY MACHINERY MANUFACTURE CO.,L.TD.

Address: Fujian Taiwanese Investment Area

Domestic Sales Tel: 0086-595-27393198 27393199 Fax: 0086-595-27393200

Email: office@socmachinery.com

International Sales Tel: 0086-592-5650603 Fax: 0086-592-5650876

Email: sales@everma.com.cn jackson@socmachinery.com Website: www.socmachinery.com www.lifttruckchina.com

Customer Service Hotline / 400-0068-123