

# CR 55 4-WAY

## Truck Mounted Forklift

**PALFINGER**



### Increased accessibility

The PALFINGER CR 55 4-WAY Truck Mounted Forklift features the unique center seating position which gives the operator easier on-and-off access, a more stable feel, and much better view for judging load centers or mounting the truck. Transition to 4-way operation is enabled via hydraulic lever while parked. The CR 55 4-WAY has the shortest 4-WAY truck mounted overhang in the industry (57"). Light weight plus a center of gravity moved closer to the truck axle puts less stress on the truck or trailer.

<https://forklift-manuals.jimdofree.com>

Reliable and efficient

PALFINGER Inc.  
 7942 Dorchester Rd.  
 Niagara Falls, ON L2E 6V6  
 Canada  
 Tel. 905-374-3363  
 Fax 905-374-1203  
 Toll Free 800-567-1554  
 www.palfinger-northamerica.com

CR 55 4W  
 04.12

**CR 55 4-WAY Truck Mounted Forklift**



**Technical Specifications**

Capacity at 24" (600 mm) Load Center	5500 lbs	2500 kg
Lift Height	122" / 146"	3100mm / 3700 mm
Diesel Engine	64 HP	47.8kW
Rated Speed	2800 rpm	2800 u/min
Lighting System for Transport (Truck)	12V	74Ah
Electronic System (Forklift)	12V	74Ah
Driven Wheels	3	
Steering	Hydrostatic	
Max. Speed	7.5 mph	12 km/h
Theoretical Gradability	30%	
Turning Circle Diameter Wall to Wall	80"	2032 mm
Dead weight (Dry Weight, Without Forks)	5654 lbs / 5830 lbs	2570 kg / 2650 kg
Working Pressure	2943 psi	205 bar
Overhang on the Vehicle	57"	1450 mm
Tire Dimension Front	10" x 16.5"	
Tire Dimensions Back	31" x 15.5" x 15"	
Fuel Capacity	10.6 US gal	40 liter



Applications shown in the leaflet do not always correspond to the standard specifications. Design and specification are subject to change without prior notice.

<https://forklift-manuals.jimdofree.com>  
[www.palfinger-northamerica.com](http://www.palfinger-northamerica.com)